



- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X = ±0.4  
X.XX = ±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. RATING: 12VDC, 50mA
  - ▲ 5. OPERATING FORCE: 260±50gf
  6. TRAVEL: 0.25mm ±0.15
  7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
  8. MECHANICAL/ELECTRICAL LIFE: 130g > 50,000 CYCLES
  - ▲ 9. SILVER CONTACT
  10. PACKAGING: TAPE & REEL; 2300 PIECES PER REEL.
  11. ▲ DENOTES CRITICAL PARAMETER



B	22924	drawing update	7/10/17	MW
A	16309	NEW RELEASE	8/14/06	RC
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3330AF260QG				
SCALE	DATE	DR	DWG	REV
8:1	6/14/2006	RC	P010951	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED