



<b>Title of Change:</b>	Final PCN for wire change from gold to copper and part number change.																													
<b>Proposed first ship date:</b>	20 July 2015																													
<b>Contact information:</b>	Contact your local ON Semiconductor Sales Office or < Yasuhiro Igarashi @onsemi.com >																													
<b>Samples:</b>	Contact your local ON Semiconductor Sales Office																													
<b>Additional Reliability Data:</b>	Contact your local ON Semiconductor Sales Office or < Kazutoshi.Kitazume@onsemi.com >.																													
<b>Type of notification:</b>	<p>This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change.</p> <p>ON Semiconductor will consider this change approved unless specific conditions of acceptance are provided in writing within 30 days of receipt of this notice. To do so, contact &lt;PCN.Support@onsemi.com&gt;.</p>																													
<b>Change Part Identification:</b>	<p>Affected products will be identified with new part number (changing suffix to "-W").</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>PART_ID</th> <th>New Part_ID</th> </tr> </thead> <tbody> <tr> <td>SCH1330-TL-H</td> <td>SCH1330-TL-W</td> </tr> <tr> <td>SCH1331-S-TL-H</td> <td rowspan="2">SCH1331-TL-W</td> </tr> <tr> <td>SCH1331-TL-H</td> </tr> <tr> <td>SCH1332-TL-H</td> <td>SCH1332-TL-W</td> </tr> <tr> <td>SCH1337-TL-H</td> <td>SCH1337-TL-W</td> </tr> <tr> <td>SCH1430-TL-H</td> <td rowspan="2">SCH1430-TL-W</td> </tr> <tr> <td>SCH1433-S-TL-H</td> </tr> <tr> <td>SCH1433-TL-H</td> <td>SCH1433-TL-W</td> </tr> <tr> <td>SCH1436-TL-H</td> <td>SCH1436-TL-W</td> </tr> <tr> <td>SCH1439-TL-H</td> <td>SCH1439-TL-W</td> </tr> </tbody> </table>			PART_ID	New Part_ID	SCH1330-TL-H	SCH1330-TL-W	SCH1331-S-TL-H	SCH1331-TL-W	SCH1331-TL-H	SCH1332-TL-H	SCH1332-TL-W	SCH1337-TL-H	SCH1337-TL-W	SCH1430-TL-H	SCH1430-TL-W	SCH1433-S-TL-H	SCH1433-TL-H	SCH1433-TL-W	SCH1436-TL-H	SCH1436-TL-W	SCH1439-TL-H	SCH1439-TL-W							
PART_ID	New Part_ID																													
SCH1330-TL-H	SCH1330-TL-W																													
SCH1331-S-TL-H	SCH1331-TL-W																													
SCH1331-TL-H																														
SCH1332-TL-H	SCH1332-TL-W																													
SCH1337-TL-H	SCH1337-TL-W																													
SCH1430-TL-H	SCH1430-TL-W																													
SCH1433-S-TL-H																														
SCH1433-TL-H	SCH1433-TL-W																													
SCH1436-TL-H	SCH1436-TL-W																													
SCH1439-TL-H	SCH1439-TL-W																													
<b>Change category(s):</b>	<input type="checkbox"/> Wafer Fab Change <input checked="" type="checkbox"/> Assembly Change <input type="checkbox"/> Test Change <input type="checkbox"/> Manufacturing Site Change/Addition <input type="checkbox"/> Manufacturing Process Change <input checked="" type="checkbox"/> Material Change <input type="checkbox"/> Product specific change <input type="checkbox"/> Datasheet/Product Doc change <input type="checkbox"/> Shipping/Packaging/Marking <input type="checkbox"/> Other: _____																													
<b>Sites Affected:</b>	<input type="checkbox"/> All site(s) <input type="checkbox"/> not applicable <input checked="" type="checkbox"/> ON Semiconductor site(s) : <input type="checkbox"/> External Foundry/Subcon site(s):	<u>Site 1</u>  ON Shenzhen, China	<u>Site 2</u>																											
<b>Description and Purpose:</b>	<p>This is a Final Process Change Notification to announce for below contents.</p> <p>1) Changing wire material from gold to copper</p> <p>2) Changing part number from XXXXXX-TL-H to XXXXXX-TL-W.</p>																													
<b>Reliability Data Summary:</b>	<table border="1"> <thead> <tr> <th>Test</th> <th>Conditions</th> <th>Results</th> </tr> </thead> <tbody> <tr> <td>Steady State Operating Life</td> <td>Tj=150degC</td> <td>1000 hrs   Pass</td> </tr> <tr> <td>High Temperature Reverse Bias</td> <td>Ta=150degC,VR=max</td> <td>1000 hrs   Pass</td> </tr> <tr> <td>Temp Humidity Storage</td> <td>Ta=85degC, RH=85%</td> <td>1000 hrs   Pass</td> </tr> <tr> <td>Temperature Cycle</td> <td>Ta=-55degC to 150degC 30min each</td> <td>100 cycles   Pass</td> </tr> <tr> <td>Pressure Cooker</td> <td>Ta=121degC,2.03x10<sup>5</sup>Pa,100%</td> <td>50 hrs   Pass</td> </tr> <tr> <td>High Temperature Storage</td> <td>Ta=150degC</td> <td>1000 hrs   Pass</td> </tr> <tr> <td>Resistance to Soldering heat(Reflow)</td> <td>Solder Temp.:260degC±5degC</td> <td>10s   Pass</td> </tr> <tr> <td>Solderability</td> <td>Solder Temp.: 245degC±5degC</td> <td>5 s   Pass</td> </tr> </tbody> </table>			Test	Conditions	Results	Steady State Operating Life	Tj=150degC	1000 hrs   Pass	High Temperature Reverse Bias	Ta=150degC,VR=max	1000 hrs   Pass	Temp Humidity Storage	Ta=85degC, RH=85%	1000 hrs   Pass	Temperature Cycle	Ta=-55degC to 150degC 30min each	100 cycles   Pass	Pressure Cooker	Ta=121degC,2.03x10 <sup>5</sup> Pa,100%	50 hrs   Pass	High Temperature Storage	Ta=150degC	1000 hrs   Pass	Resistance to Soldering heat(Reflow)	Solder Temp.:260degC±5degC	10s   Pass	Solderability	Solder Temp.: 245degC±5degC	5 s   Pass
Test	Conditions	Results																												
Steady State Operating Life	Tj=150degC	1000 hrs   Pass																												
High Temperature Reverse Bias	Ta=150degC,VR=max	1000 hrs   Pass																												
Temp Humidity Storage	Ta=85degC, RH=85%	1000 hrs   Pass																												
Temperature Cycle	Ta=-55degC to 150degC 30min each	100 cycles   Pass																												
Pressure Cooker	Ta=121degC,2.03x10 <sup>5</sup> Pa,100%	50 hrs   Pass																												
High Temperature Storage	Ta=150degC	1000 hrs   Pass																												
Resistance to Soldering heat(Reflow)	Solder Temp.:260degC±5degC	10s   Pass																												
Solderability	Solder Temp.: 245degC±5degC	5 s   Pass																												



**Electrical Characteristic Summary:**

Electrical characteristics are not impacted.

**List of Affected Standard Parts:**

- SCH1330-TL-H
- SCH1331-S-TL-H
- SCH1331-TL-H
- SCH1332-TL-H
- SCH1337-TL-H
- SCH1430-TL-H
- SCH1433-S-TL-H
- SCH1433-TL-H
- SCH1436-TL-H
- SCH1439-TL-H